


NEW

IF YOU NEED TO MEASURE:

lx, Watt/m², CRI, CCT, Color


dominant wavelength



Light measurement simplified

GL SPECTROLUX

Rapidly growing number of replaced old lighting systems with the comprehensive, energy efficient lighting solution based on LED, requires quick and reliable measurements. In European R&D Center, GL Optic developed a new portable device, GL Spectrolux, for immediate testing of new lighting installations. Thanks this new instrument, a user will be able to examine photometric and colorimetric properties of the upgraded lighting system.



GL Optic products are made in Europe, sold and serviced on all continents.

Affordable, performance just got easy to use

The GL Spectrolux handheld spectral lux meter sets new price standards. Based on our popular Spectis 1.0 Touch, it evaluates light quantities such as lux, CRI, CCT, color and more in a compact handheld package. The GL Spectrolux includes a laboratory Class B measurement head for superior accuracy and repeatability. Each device is individually calibrated and traceable to international reference standards.

IF YOU NEED TO MEASURE:

- **Illumination value** – Lux
- **Color rendering index according to CIE** – CRI
- **Correlated color temperature according to CIE standard** – CCT
- **Color coordinates according to CIE 1931 and CIE 1960** – COLOR and more...

IDEAL LIGHT MEASUREMENT SOLUTION ADDRESSED TO:



**LIGHT DESIGNERS
and ARCHITECTS**



**LAMP
MANUFACTURERS**



**PHOTOGRAPHERS
and CINEMATOGRAPHERS**

APPLICATIONS:

FACTORIES and OFFICES

HOTELS and SHOPS

SCHOOLS & HOSPITALS

STREET LAMP MEASUREMENTS

THEATER & CINEMA LIGHTING

STRUCTURES and LANDSCAPES



FEATURES:

- Unmatched accuracy and performance
- Intuitive button operation
- Color LCD screen
- USB connectivity
- Internal storage for > 20,000 measurements



TECHNICAL DATA SHEET

Illuminance	1 – 200,000 lx
Spectral range	340 – 780 nm
Cosine correction	Class B according to DIN 5032 Part 7
Detector	CMOS image sensor
Number of pixels	256
Physical resolution	~ 1.7 nm
Wavelength reproducibility	0.5 nm
Spectroradiometric accuracy	4%
Measurement uncertainty of color coordinates (x,y)	0.0015
Integration time	10 ms – 10 s
A/D conversion	16 bits
Signal to noise ratio	1000:1
Stray light	2*10E-3
Display	2.8" color LCD 240x320 px
USB	USB 2.0
Power	lithium-ion battery 1400 mAh
Power consumption	~ 640 mA
Power supply	Input: AC 100-240V 50/60 Hz 0.15 A
Ambient temperature	5 – 35°C
Dimensions	75 mm x 155 mm x 20 mm
Weight	280 g (< 1 pound)

GL SPECTROSOFT

A complete software suite to analyze, interpret and present your results.

GL SPECTROSOFT is an optional software portfolio that adds power, speed and efficiency to your GL Spectrolux. Whether analyzing field measurements, comparing lighting scenarios, or supporting production quality control, this versatile, modular, upgradable software platform provides quick access to useful information. Advanced features include configurable pass/fail criteria and structure reporting formats to simplify presentation and sharing of results.



	BASIC	PRO	LAB
Graphical spectra	•	•	•
Results window with calculations			
• Color coordinates $ x\ y \ u\ v u' \ v'$			
• CRI, Ra, R1-R14			
• Peak wavelength,	•	•	•
• Dominant wavelength,			
• Lambda 2,			
• Purity			
Export / Import in TXT format	•	•	•
Reports	•	•	•
Report editor RTF		•	•
Chromaticity charts - Color diagrams according to CIE			
• 1931 (x y)	•	•	•
• 1960 (u v)			
• 1976 (u'v')			
Window with selected results		•	•
Comparison window		•	•
Binning Tool		•	•
Measurement according to ISO 3664		•	•
Metamerism indices in VIS range		•	•
Calculate intensity values [cd]		•	•
MacAdam Ellipses		•	•
Transmission or reflection measurements of optical components		•	•
Calculating scotopic / photopic values		•	•
TM-30-15		•	•
Set automatic measurements schedule		Add-ON*	•
RELATIVE measurements comparison		Add-ON*	•
Set of parameters as criteria for PASS/FAIL selection		Add-ON*	•
Change the spectral range of a calculation		Add-ON*	•
Compensating the influence of ambient light		Add-ON*	•
Calculations of PPF/D/PAR		Add-ON*	•
GL Spectrosoft Automation		Add-ON*	Add-ON*

*Optional software features available on demand

CONTACT US:

GERMANY

JUST Normlicht GmbH
Vertrieb + Produktion
Tobelwasenweg 24
D-73235 Weilheim/Teck
Phone: +49 7023 9504 0
Fax: +49 7023 9504 52
info@just-normlicht.de

FRANCE

JUST Normlicht France Sàrl
3, Rue Louis Pasteur
67240 Bischwiller
Phone: +33 (0)3 8806 2822
Fax: +33 (0)3 8806 2823
info@just-normlicht.fr

USA

JUST Normlicht Inc.
2000 Cabot Blvd. West Suite 120
Langhorne, PA 19047-2408
United States
Phone: +1 267 852-2200
Fax: +1 267 852-2207
sales@justnormlicht.com

POLAND

GL Optic R&D Center Sp. z o.o.
ul. Poznańska 70
62-040 Puszczykowo
Phone: +48 61 819 40 03
office@gloptic.com