



# ZetaView<sup>®</sup> MONO

## Technical Data




Subpopulations




Size



Fluorescence



Zeta Potential



Concentration



Colocalization

# Technical Data: PMX-130 ZetaView Mono Laser



## Dimensions

<b>Physical</b>	<ul style="list-style-type: none"><li>• Footprint (W x D x H): 20 × 30 × 25cm</li><li>• Weight: 8.5kg (main unit, PC and monitor extra)</li><li>• Shipping box with standard content:<ul style="list-style-type: none"><li>Main unit: 51 × 32 × 77cm; 16,9 kg to 18,5 kg*</li><li>Minimum 22" Monitor: 61 × 18 × 48cm; 7,42 kg</li></ul></li></ul>
<b>Electrical</b>	<ul style="list-style-type: none"><li>• 90-240V, 47-63Hz, 50VA</li></ul>

## Warranty & Support

<b>Warranty</b>	<ul style="list-style-type: none"><li>• 1 year (glass excluded)</li></ul>
<b>Service &amp; Support</b>	<ul style="list-style-type: none"><li>• Reaction time: 48 hours</li><li>• Maintenance, service and IQ/OQ contracts can be purchased on request</li><li>• Support via telephone, e-mail and remote desktop software software for trained users free of charge during warranty period</li><li>• Training courses for new users available on demand</li><li>• Special arrangements and specifications can be purchased on request – quotation required</li></ul>

\* With zeta potential and/or fluorescence option

# Technical Data: PMX-130 ZetaView Mono Laser



## General Features

<b>Measurement Principle</b>	<ul style="list-style-type: none"><li>• Precision-engineered motorized scanning Nanoparticle Tracking Analysis (NTA) instrument for tracking the movement of individual visualized nanoparticles in suspension</li><li>• Real-time visualization of Brownian Motion and Electrophoretic Mobility, for measuring size, concentration and zeta potential in scatter and fluorescence mode*</li><li>• One software-controlled laser for enhanced fluorescence measurements*</li><li>• Software controlled 11-position fluorescence emission filter wheel for quick changes between scatter and fluorescence measurements as well as between different emission filters*</li><li>• Fast scanning to acquire and analyze typically more than 2000 particles in less than one minute</li><li>• Two software-controlled pumps for liquid transport and sample dosing</li></ul>
<b>Samples</b>	<ul style="list-style-type: none"><li>• Nanoparticles suspended in polar liquids and organic solvents (e.g. water, biological buffers, alcohols) for size, concentration, fluorescence and zeta potential studies*</li></ul>

## Hardware

<b>Equipment</b>	<ul style="list-style-type: none"><li>• ZetaView® PMX-130 main unit is equipped with a fixed NTA cell assembly, laser (see section Lasers) and bottles for buffer rinse</li><li>• Two software-controlled pumps for liquid transport and sample dosing</li><li>• Power of statistics by automated unique scan and dose control for measurement of 1 - 100 independent sub volumes</li><li>• Zeta potential option*</li><li>• fluorescence option features short acquisition times to avoid negative effect of photo bleaching*</li></ul>
<b>Optical Layout</b>	<ul style="list-style-type: none"><li>• 90° laser scattering video microscope with x10 magnification for maximized sample volume and highest statistics</li><li>• Automated alignment and focusing of laser and microscope</li></ul>
<b>Camera</b>	<ul style="list-style-type: none"><li>• High sensitive CMOS camera 640 × 480 pixels</li><li>• Variable frame rate from 2 to 60 Hz for optimum resolution and fast acquisition</li></ul>
<b>Lasers</b>	<ul style="list-style-type: none"><li>• Available laser wavelengths: 405 nm, 488 nm, 520 nm, 640 nm, and 660 nm at typical laser power of &gt;30 mW</li><li>• Pulse duration 0.1 ms up to continuous</li></ul>
<b>Fluorescence</b>	<ul style="list-style-type: none"><li>• Long wave-pass (LWP) cut-off filters: @405 nm: 430 nm @488 nm: 500 nm @520 nm: 550 nm @640 nm: 680 nm @660 nm: 680 nm</li><li>• Customized LWP and bandpass filter available on request</li></ul>
<b>Cleaning</b>	<ul style="list-style-type: none"><li>• Tool-free access to glass cuvette for quick and simple cleaning process</li><li>• Cell cleaning recommended weekly or monthly depending on sample type and usage</li><li>• Cleaning of driver electrodes required after &gt;1000 zeta potential runs*</li><li>• Cleaning kit and spare parts included in delivery</li></ul>
<b>Temperature Range/Control</b>	<ul style="list-style-type: none"><li>• External working temperature range: 5°C to 45°C</li><li>• Sample temperature control: Peltier temperature control from RTP -5°C to 55°C with automated dew-point sensing</li></ul>

\* With zeta potential and/or fluorescence option

# Technical Data: PMX-130 ZetaView Mono Laser



## Computer System

<b>Control Device</b>	<ul style="list-style-type: none"> <li>• Intel® NUC Mini PC</li> <li>• 250 GB SSD hard drive</li> <li>• Windows 10 Professional</li> <li>• Maclean holder for mounting computer at backside of screen</li> <li>• Keyboard and mouse</li> </ul>
<b>Monitor</b>	<ul style="list-style-type: none"> <li>• 22" LED screen (or better)</li> </ul>

## Software

<b>Communication</b>	<ul style="list-style-type: none"> <li>• Software provided on pre-configured PC, communication via Ethernet</li> </ul>
<b>Quality Control</b>	<ul style="list-style-type: none"> <li>• Cell quality check, daily performance check, outlier control with automatic Grubbs statistical analysis of measurement data</li> </ul>
<b>Live Monitoring</b>	<ul style="list-style-type: none"> <li>• Number of detected particles in scatter and fluorescence mode*, scattering intensity, conductivity*, temperature, particle drift</li> </ul>
<b>Standard Operating Procedures (SOP)</b>	<ul style="list-style-type: none"> <li>• Fully-customizable SOPs for different samples/applications</li> </ul>
<b>Analysis and Reports</b>	<ul style="list-style-type: none"> <li>• Data Analysis: particle size distribution profiles, concentrations, overlays and averaging, scatter plots, zeta potential distribution profiles, sub-population analysis (using additional 'Particle Explorer' software)</li> <li>• Data export format: AVI, TXT, CSV, FCS, PDF reports containing key results</li> </ul>

## Measurement Specifications

<b>Size/Concentration</b>	<ul style="list-style-type: none"> <li>• Concentration range: <math>10^5 - 10^9</math> particles/ml</li> <li>• Particle size: 10nm – 1000nm (dependent on sample and laser selection)</li> <li>• Accuracy: <math>\pm 5</math>nm (for 100nm polystyrene latex)</li> <li>• Reproducibility: <math>\pm 2</math>nm (for 100nm polystyrene latex)</li> </ul>
<b>Fluorescence*</b>	<ul style="list-style-type: none"> <li>• Concentration range: <math>10^5 - 10^9</math> particles/ml</li> <li>• Particle size: 20nm – 1000nm (dependent on fluorescent dye and laser selection)</li> <li>• Accuracy: <math>\pm 5</math>nm (for 100nm polystyrene latex)</li> <li>• Reproducibility: <math>\pm 2</math>nm (for 100nm polystyrene latex)</li> </ul>
<b>Zeta Potential*</b>	<ul style="list-style-type: none"> <li>• Working range: -500 to +500mV</li> <li>• Concentration range: <math>10^6 - 10^{10}</math> particles/ml</li> <li>• Particle size: 20nm – 5000nm (dependent on sample and laser selection)</li> <li>• Conductivity range: 3<math>\mu</math>S/cm – 15mS/cm</li> <li>• Accuracy: <math>\pm 4</math>mV (zeta potential standard)</li> <li>• Reproducibility: <math>\pm 2</math>mV (zeta potential standard)</li> </ul>
<b>General</b>	<ul style="list-style-type: none"> <li>• Minimum sample quantity: 500<math>\mu</math>l of sample at <math>10^5</math> particles/ml</li> <li>• pH range: 1 – 13</li> <li>• Temperature: 5°C to 45°C (external temperature)</li> <li>• Sample volume visualised and tracked by the camera for a single measurement: 11 <math>\times</math> 3.3 nL</li> </ul>
<b>Reference Materials</b>	<ul style="list-style-type: none"> <li>• Nominal 100 nm reference suspension for size</li> <li>• Nominal 100 or 200 nm reference suspension for fluorescence*</li> <li>• Nominal -50mV reference suspension for zeta potential*</li> </ul>

\* With zeta potential and/or fluorescence option

Manufactured by Particle Metrix, distributed in the UK/Ire by **analytik**.